

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : F02B 11/00, F02D 15/04, 41/04, 43/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/28198</p>
<p>(21) International Application Number: PCT/SE99/01929</p>	<p>(22) International Filing Date: 26 October 1999 (26.10.99)</p>	<p>(43) International Publication Date: 18 May 2000 (18.05.00)</p>
<p>(30) Priority Data: 9803666-8 26 October 1998 (26.10.98) SE</p>	<p>(81) Designated States: JP, KR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report. In English translation (filed in Swedish).</p>	
<p>(71) Applicant (for all designated States except US): AB VOLVO [SE/SE]; S-405 08 Gothenburg (SE).</p>		
<p>(72) Inventor; and (75) Inventor/Applicant (for US only): DENBRATT, Ingemar [SE/SE]; Bofinksvägen 3, S-429 33 Kullavik (SE).</p>		
<p>(74) Agents: BERG, S., A. et al.; Albihns Patentbyrå Stockholm AB, P.O. Box 5581, S-114 85 Stockholm (SE).</p>		
<p>(54) Title: METHOD OF CONTROLLING THE PROCESS OF COMBUSTION IN AN INTERNAL COMBUSTION ENGINE, AND ENGINE WITH MEANS FOR VARYING THE EFFECTIVE COMPRESSION RATIO OF THE CYLINDERS</p>		
<p>(57) Abstract</p>		
<p>Four-stroke internal combustion engine with variable geometric compression ratio, electrically operated inlet valves and means for supplying a homogeneous fuel/air mixture to the engine cylinders. The inlet valves (9) and the compression ratio are controlled by a control unit (15), so that the fuel/air mixture, within a lower engine rpm range, is compressed to self-ignition.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Method of controlling the process of combustion in an internal combustion engine, and engine with means for varying the effective compression ratio of the cylinders

5 The present invention relates to a method of controlling the combustion process in a combustion chamber in an internal combustion engine with at least one cylinder having at least one inlet valve and one exhaust valve, means for varying the geometric compression ratio of the cylinder and means for supplying a homogeneous fuel/air mixture to the combustion chamber.

10

The invention also relates to a four-stroke internal combustion engine with at least one cylinder having at least one inlet valve and one exhaust valve, means for varying the geometric compression ratio of the cylinder as well as means for supplying a homogeneous fuel/air mixture to the combustion chamber of the cylinder.

15

For homogeneous charge compression ignition (HCCI) in a four-stroke internal combustion engine, a homogeneous diluted (with extra air or residual gas) fuel/air mixture is compressed to self-ignition. The advantage of this compared to first compressing the inlet air and then injecting fuel into the combustion chamber (the diesel process) is that the entire fuel/air mixture burns simultaneously and not successively as when a flame front propagates through the combustion chamber from a sparkplug or injector. This creates a homogeneous temperature in the combustion chamber, which in turn makes it possible to achieve, for example in an unthrottled Otto-engine at partial load, the efficiency of the diesel engine but without the high nitrogen oxide and particle emissions of the diesel engine. The nitrogen emissions can be reduced from ca. 1000 ppm to as little as 10-20 ppm. The particle emissions of the diesel engine can be reduced to the same level as those of the Otto-engine. The difficulty is, however, to control the combustion since it is kinetically controlled. If the mixture is too rich, the energy released will be too rapid (knocking), and if it is too lean, ignition will be made impossible. In an HCCI Otto-engine with gasoline as

20

25

30

fuel, a high and controlled temperature is required to achieve self-ignition, and this can be achieved with high compression ratio and/or by heating the inlet air. In an HCCI diesel engine with diesel oil as fuel, lower temperatures are required than with a normal diesel engine, which means that the compression ratio must be lowered.

The difficulty up to now in HCCI-engines has been to control the ignition delay (the cylinder temperature) in such a manner that the combustion is positioned correctly about the top dead centre at various rpm:s and loads, and this has greatly reduced the range of use of such engines. Especially control problems during transients, where the cylinder temperature must be checked from one cycle to the next, has limited the range of use of HCCI-engines to generators, for example, where the drive unit operates with very small variations in rpm and load.

The purpose of the present invention is to achieve a method of controlling the temperature in the cylinders in an HCCI-engine, so that the ignition time will be correct at various engine speeds and loads, thereby making it practically possible to use HCCI-engines in motor vehicles, thereby reducing their fuel consumption and emissions.

This is achieved according to the invention by virtue of the fact that the compression ratio and the closing of the inlet valve are controlled so that the mixture, at least within a lower rpm range, is compressed to self-ignition.

Complete freedom of valve control, so that the opening and closing time can also be freely controlled from cycle to cycle, can be achieved by using electromagnetically operated valves. The compression ratio can be varied in a known manner by virtue of the fact that the engine cylinder communicates with an additional cylinder containing a movable plunger by means of which the total volume of the combustion chamber can be varied.

An HCCI-engine which must be able to operate within a wide rpm range, e.g. with an upper rpm limit of about 6000 rpm, is preferably equipped with an ignition system which is controlled so that it is deactivated within said lower rpm range, the upper limit of which can lie between 3000 and 4000 rpm. When this limit is exceeded, the ignition system is activated at the same time as the control of the inlet valve is changed and the compression ratio is reduced to normal engine operation.

An internal combustion engine of the type described by way of introduction, which is to be controlled in the manner described above, is characterized in that at least the inlet valve has variable valve times and that the control means are arranged to control the degree of opening of the inlet valve and the compression ratio of the cylinder as a function of engine speed and load, so that the mixture, at least within a lower engine speed range, is compressed to self-ignition.

The method according to the invention will be described below with reference to the accompanying drawings, where Figs. 1- 4 show schematically a cylinder with associated piston in a four-stroke internal combustion engine with variable compression ratio.

In Fig. 1, 1 designates a cylinder in the engine block of a four-stroke internal combustion engine, which in the example shown is an Otto-engine, having a sparkplug 2 projecting into the combustion chamber 3. The cylinder 1 has a piston 4, which is connected via a connecting rod 5 to a throw 6 on the crankshaft 7. The combustion chamber 3 has an inlet 8 for supply of fuel/air mixture. An inlet valve 9 is arranged in the inlet port of the combustion chamber. An exhaust valve (not shown) is arranged in an outlet port to the exhaust conduit.

The opening and closing of the inlet valve 9 is electromagnetically controlled with the aid of an electromagnetic device 12. The valve can be of a type which is known per se with a valve spindle joined to a metal disc located between two electromag-

nets. The electromagnets are magnetized alternatingly and the metal disc is drawn towards that magnet which is momentarily magnetized. With electromagnetically controlled valves of this known type, the degree of opening of the valves can be freely controlled, both from cycle to cycle and for individual cylinders. The spark-
5 plug 2 is joined to an ignition system 14 with a control unit into which, i.a., signals representing engine rpm and accelerator pedal position are fed for controlling the ignition as a function of engine rpm and load. The electromagnets of the valve 9 are controlled by a control unit 15 into which there is fed a signal from a sensor (not
10 shown), which directly or indirectly measures the pressure P in the cylinder chamber, and/or a signal representing the ion flow. This signal can be obtained with the sparkplug as a sensor.

The control unit 15 also controls the compression ratio in the cylinder 1 by regulating the position of a plunger 16 in a cylinder 17 communicating with the cylinder 1.
15 The position of the plunger 16 in the cylinder is controlled by operating means 18, which, for example, can be of the type shown and described in SE-A-405 993.

Figs. 1- 4 show HCCI-operation, i.e. the ignition system is deactivated and ignition of the fuel/air mixture supplied to the combustion chamber 3 is effected by self-
20 ignition during compression of the mixture. Fig. 1 illustrates the position of the plunger 16 at maximum compression ratio and the position IS of the piston 4, when the inlet valve 9 closes during the compression stroke at low load and high rpm within the low rpm range (i.e. up to ca. 3000-4000 rpm). During a transient state to higher load and lower rpm from the operating state in Fig. 1, the effective compression ratio is reduced, firstly, by pulling the plunger 16 back, as indicated by the
25 arrow, so that the geometric compression ratio is reduced, and, secondly, by delaying the closing of the inlet valve 9. In Fig. 3, the position IS of the piston 4 is illustrated when the inlet valve 9 closes at higher load and lower rpm. As a comparison will show, the closing time is approximately the same as for the state in Fig. 1. The
30 compression ratio, however, has been lowered by the plunger 16 being pulled back

to increase the total volume of the combustion chamber. During a transient to lower load and higher rpm (Fig. 4) from the operating state in Fig. 3, the effective compression ratio is increased, firstly, by moving the plunger 16 forward, as indicated by the arrow on the plunger 16, so that the geometric compression ratio increases, and, secondly, by closing the inlet valve 9 earlier. In Fig. 4, the inlet valve 9 closes at the bottom dead centre of the piston 4.

When the rpm exceeds the upper limit of the lower rpm range, e.g. at ca. 4000 rpm, for a passenger car with a top end rpm of ca. 6000-8000 rpm, the control is switched to normal Otto-engine operation, i.e. with a normal compression ratio and valve overlap, at the same time as the ignition system is activated. This switch also occurs when the engine load exceeds 50-70% of the maximum engine load. A "normal" compression ratio can be ca. 8-10:1 and the maximum compression ratio under HCCI-operation is ca. 16-20:1.





The effective compression ratio can be regulated by varying the geometric compression ratio or by varying the point in time when the inlet valve closes, or by a combination of these two. The exhaust valve (not shown) can be electromagnetically operated as is the inlet valve, but since the control during HCCI-operation does not require variable valve timing for the exhaust valve, it can be camshaft-controlled in a conventional manner.

Claims

1. Method of controlling the combustion process in the combustion chamber (3) of a four-stroke internal combustion engine with at least one cylinder (1) having at least one inlet valve (9) and one exhaust valve (11), means (16,17,18) for varying the geometric compression ratio of the cylinder, and means for supplying a homogeneous fuel/ air mixture to the combustion chamber, **characterized** in that the compression ratio and the closing of the inlet valve (9) are controlled so that the mixture, at least within a lower rpm range, is compressed to self-ignition.
2. Method according to claim 1, **characterized** in that the compression ratio and the closing of the inlet valve (9) are controlled so that the compression ratio will be higher and the valve close earlier at low loads and high engine speed than at high loads and low engine speed, that the compression ratio is reduced and the closing of the valve is set later in transient states to high load and low engine speed, and that the compression ratio is raised and the valve is closed earlier in transient states to low load and high engine speed.
3. Method according to claim 1 or 2 when controlling the combustion process in an internal combustion engine with means (2,14) for spark ignition of the fuel/air mixture in the combustion chamber, **characterized** in that the spark ignition means (2,14) are held deactivated within said lower engine speed range and are activated when the speed of the engine exceeds the upper limit of the lower engine speed range, at the same time as the geometric compression ratio is controlled towards a low level.
4. Method according to one of claims 1-3, **characterized** in that at least the inlet valve (9) is controlled by electromagnetic means (12).

5. Method according to one of claims 1- 4, **characterized** in that gasoline is used as fuel.
6. Method according to one of claims 1-5, **characterized** in that the geometric compression ratio and the closing of the inlet valve (9) are controlled so that the highest effective compression ratio is approximately twice the lowest effective compression ratio.
7. Four-stroke internal combustion engine with at least one cylinder having at least one inlet valve and one exhaust valve, means for varying the geometric compression ratio of the cylinder and means for supplying a homogeneous fuel/air mixture to the combustion chamber of the cylinder, **characterized** in that at least the inlet valve has variable valve times and that the control means (12,15,18) are arranged to control the degree of opening of the inlet valve (9) and the compression ratio of the cylinder (1) as a function of engine speed and load, so that the mixture, at least within a lower engine speed range, is compressed to self-ignition.
8. Engine according to claim 7, **characterized** in that the control means (12,15,18) are arranged to control the compression ratio and the closing of the inlet valve (9), so that the compression ratio becomes higher and the valve closes earlier at low loads and high engine speed than at high loads and low engine speed, that the compression ratio is reduced and the valve closes later in transient states to high load and low engine speed, and that the compression ratio is raised and the valve closes earlier in transient states to low load and high engine speed.
9. Engine according to claim 7 or 8, **characterized** in that the inlet valve (9) and the means for varying the geometric compression of the cylinder (1) have operating means (12,18), coupled to a control unit (15), which controls the operating means as a function of various control signals fed to the control unit.

10. Engine according to claim 9, **characterized** in that the inlet valve (9) has electromagnetic operating means (12).
- 5 11. Engine according to claim 10, **characterized** in that the control unit (15) is connected to an ion flow signal sensor arranged in the combustion chamber (3) and to a tachometer.
- 10 12. Engine according to claim 10, **characterized** in that the control unit (15) is connected to a pressure signal sensor arranged in the combustion chamber (3).
- 15 13. Engine according to one of claims 7-12 with an ignition system (2,14) comprising at least one sparkplug (2) for each cylinder and an ignition control device (14), which is connected to a tachometer and an accelerator pedal position sensor, **characterized** in that the ignition control device (14) is disposed to keep the sparkplug (2) deactivated within said lower engine speed range and to activate the sparkplug when the engine speed exceeds the upper limit of the lower engine speed range, and that the control unit (15) is arranged to then, firstly, control the inlet valve (9) and the exhaust valve, so that the inlet valve begins to open before
20 the exhaust valve is completely closed, and, secondly, to control the geometric compression ratio towards a low level.



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/01929

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: F02B 11/00, F02D 15/04, F02D 41/04, F02D 43/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: F02B, F02D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9810179 A2 (CUMMINS ENGINE COMPANY, INC.), 12 March 1998 (12.03.98), page 7 - page 8, figure 1, abstract --	
A	US 5476072 A (E.G. INVENTOR), 19 December 1995 (19.12.95), figure 1, abstract --	
A	EP 0879955 A2 (NISSAN MOTOR COMPANY, LIMITED), 25 November 1998 (25.11.98), figure 1, abstract --	
A	US 4768481 A (C.D. WOOD), 6 Sept 1988 (06.09.88), figures 4,5, abstract --	

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 January 2000

Date of mailing of the international search report

17-02-2000

Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer
 Dan Ionesco / JA A
 Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/12/99

International application No.

PCT/SE 99/01929

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9810179 A2	12/03/98	AU 4082997 A AU 4158097 A EP 0928369 A WO 9807973 A	26/03/98 06/03/98 14/07/99 26/02/98
US 5476072 A	19/12/95	NONE	
EP 0879955 A2	25/11/98	JP 10318108 A JP 10331708 A	02/12/98 15/12/98
US 4768481 A	06/09/88	JP 1036917 A	07/02/89

INTERNATIONALER RECHERCHENBERICHT

Int lionales Aktenzeichen

PCT/DE 99/03112

A. KLASSIFIZIERUNG DES ANMELDUNGSGEGENSTANDES
IPK 7 H05B3/26 H05B3/28 G01N27/406

Nach der Internationalen Patentklassifikation (IPK) oder nach der nationalen Klassifikation und der IPK

B. RECHERCHIERTE GEBIETE

Recherchiertes Mindestprüfstoff (Klassifikationssystem und Klassifikationssymbole)
IPK 7 H05B G01N

Recherchierte aber nicht zum Mindestprüfstoff gehörende Veröffentlichungen, soweit diese unter die recherchierten Gebiete fallen

Während der internationalen Recherche konsultierte elektronische Datenbank (Name der Datenbank und evtl. verwendete Suchbegriffe)

C. ALS WESENTLICH ANGESEHENE UNTERLAGEN

Kategorie*	Bezeichnung der Veröffentlichung, soweit erforderlich unter Angabe der in Betracht kommenden Teile	Betr. Anspruch Nr.
A	US 4 464 244 A (UCHIDA MASAOKI ET AL) 7. August 1984 (1984-08-07) Zusammenfassung; Abbildungen 1,2 Spalte 3, Zeile 24 - Spalte 4, Zeile 28 ----	1,7
A	DE 195 22 347 C (SIEMENS AG) 19. September 1996 (1996-09-19) Zusammenfassung ----	1,7
A	US 4 559 126 A (MASE SYUNZO ET AL) 17. Dezember 1985 (1985-12-17) Zusammenfassung; Abbildungen 2,3 Spalte 4, Zeile 3 - Zeile 48 -----	1,7



Weitere Veröffentlichungen sind der Fortsetzung von Feld C zu entnehmen



Siehe Anhang Patentfamilie

* Besondere Kategorien von angegebenen Veröffentlichungen :

"A" Veröffentlichung, die den allgemeinen Stand der Technik definiert, aber nicht als besonders bedeutsam anzusehen ist

"E" älteres Dokument, das jedoch erst am oder nach dem internationalen Anmeldedatum veröffentlicht worden ist

"L" Veröffentlichung, die geeignet ist, einen Prioritätsanspruch zweifelhaft erscheinen zu lassen, oder durch die das Veröffentlichungsdatum einer anderen im Recherchenbericht genannten Veröffentlichung belegt werden soll oder die aus einem anderen besonderen Grund angegeben ist (wie ausgeführt)

"O" Veröffentlichung, die sich auf eine mündliche Offenbarung, eine Benutzung, eine Ausstellung oder andere Maßnahmen bezieht

"P" Veröffentlichung, die vor dem internationalen Anmeldedatum, aber nach dem beanspruchten Prioritätsdatum veröffentlicht worden ist

"T" Spätere Veröffentlichung, die nach dem internationalen Anmeldedatum oder dem Prioritätsdatum veröffentlicht worden ist und mit der Anmeldung nicht kollidiert, sondern nur zum Verständnis des der Erfindung zugrundeliegenden Prinzips oder der ihr zugrundeliegenden Theorie angegeben ist

"X" Veröffentlichung von besonderer Bedeutung; die beanspruchte Erfindung kann allein aufgrund dieser Veröffentlichung nicht als neu oder auf erfinderischer Tätigkeit beruhend betrachtet werden

"Y" Veröffentlichung von besonderer Bedeutung; die beanspruchte Erfindung kann nicht als auf erfinderischer Tätigkeit beruhend betrachtet werden, wenn die Veröffentlichung mit einer oder mehreren anderen Veröffentlichungen dieser Kategorie in Verbindung gebracht wird und diese Verbindung für einen Fachmann naheliegend ist

"&" Veröffentlichung, die Mitglied derselben Patentfamilie ist

Datum des Abschlusses der internationalen Recherche

11. Februar 2000

Absenddatum des internationalen Recherchenberichts

21/02/2000

Name und Postanschrift der Internationalen Recherchenbehörde

Europäisches Patentamt, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Bevollmächtigter Bediensteter

Taccoen, J-F

INTERNATIONALER RECHERCHENBERICHT

Angaben zu Veröffentlichungen, die zur selben Patentfamilie gehören

Internationales Aktenzeichen

PCT/DE 99/03112

Im Recherchenbericht angeführtes Patentdokument	Datum der Veröffentlichung	Mitglied(er) der Patentfamilie	Datum der Veröffentlichung
US 4464244 A	07-08-1984	JP 1589878 C	30-11-1990
		JP 2016467 B	17-04-1990
		JP 57211543 A	25-12-1982
		EP 0068321 A	05-01-1983
DE 19522347 C	19-09-1996	KEINE	
US 4559126 A	17-12-1985	JP 1805484 C	26-11-1993
		JP 5013261 B	22-02-1993
		JP 60036948 A	26-02-1985
		CA 1210812 A	02-09-1986
		EP 0133820 A	06-03-1985